



ANFRAGE / BESTELLFORMULAR
ENQUIRY / ORDER FORM

FORMULAIRE DE DEMANDE / COMMANDE
RICHIESTA / MODULO D'ORDINE

Combined supply and
return manifold with
intermediate insulation

HVI 80
...
HVI 500

VERTEILER GRÖSSE MAINFOLD SIZE RÉPARTITEURS TAILLE COLLETORE DIST.	ABGANGS DIMENSIONS CONNECTIONS SIZE DIMENSIONS SORTIES DIMENSIONS COLLEGAM.	MAX. VERTEILER ANSCHLÜSSE* MAX. MAINFOLD CONNECTIONS* EAU DE CHAUF- FAGE SORTIE* MAX. COLLETT- ORE ATTACCHI*	HEIZWASSER DURCHSATZ bis HOT WATER FLOW RATE up to L'EAU CHAUDE DÉBIT jusqu'à CAUDAL AGUA CALEFACCIÓN fino a	LEISTUNG BEI OUTPUT AT PUISSANCE A POTENZA CON $\Delta t=20^{\circ}\text{C}$ bis up to jusqu'à fino a
<input type="checkbox"/> 80	DN 25	DN 40	2,3-3,3 m ³ /h	50-75 kW
<input type="checkbox"/> 100	DN 32	DN 50	4-6,5 m ³ /h	90-150 kW
<input type="checkbox"/> 120	DN 50	DN 65	8,5-13 m ³ /h	190-290 kW
<input type="checkbox"/> 160	DN 65	DN 80	14-19,3 m ³ /h	315-435 kW
<input type="checkbox"/> 200	DN 80	DN 100	19,3-32 m ³ /h	435-725 kW
<input type="checkbox"/> 250	DN 100	DN 125	32-49 m ³ /h	725-1100 kW
<input type="checkbox"/> 300	DN 125	DN 200	49-86 m ³ /h	1100-1950 kW
<input type="checkbox"/> 400	DN 150	DN 200	71,8-120 m ³ /h	1625-2700 kW
<input type="checkbox"/> 500	DN 200	DN 300	120-263 m ³ /h	2700-5955 kW

Verteilerlänge Manifold length
Longueur du répartiteur Longitud distribuidor

Max. Betriebsdruck - Max. operating pressure excess
Pression de service max. - Sobrepresión de serv. máx.

Max. Vorlauf-Temperatur - Max. supply temperature
Température d'alimentation - Temp. máx. de impulsión

Isolierung mit verzinktem Stahlblechmantel, Insulated with galvanised sheet steel jacket
Isolation avec chemise en tôle d'acier zinguée, Aislamiento con camisa de chapa de acero cincada

EPS 35 mm (nur bei HVE80), EPS 35 mm (HVE80 only)
EPS 35 mm (seulement pour HVE80), EPS 35 mm (solo en HVE80)

Steinwolle 50 mm
Rock wool
Laine de roche 100 mm
Lana mineral

Wandkonsolen Standkonsolen
Wall brackets Stands
Consoles murales Consoles sur pied
Consolas murales Consolas de column

A= mm H= mm

HVI 80-120, A= 160 mm / 220 mm

*Max. Verteileranschlüsse bei Ausführungen:
*Max. manifold connections in the following configurations:
*Raccords répartiteur max. pour les versions:
*Attacchi max. collettore per i modelli:

